

SUBMERSIBLE SOLIDS HANDING PUMPS

4VL(X)P, 8VL(X)P, 8SM(X)P

RPM	1750		
MOTOR TYPE	PREMIUM EFFICIENT, IEC 60034-30 LEVEL IE3		
MOTOR DESIGN TYPE	A (3 ϕ)		
GENERAL INSULATION CLASS	H		
STATOR WINDING CLASS	H		
MAXIMUM STATOR TEMPERATURE	356°F (180°)		
MOTOR PROTECTION	BI-METALLIC, TEMPERATURE SENSITIVE DISC, SIZED TO OPEN AT 150°C AND AUTOMATICALLY RESET @ 117-89°C DIFFERENTIAL, THREE IN THREE PHASE		
ELECTRICAL RATINGS	HEAT SENSOR	24 VDC 5 AMPS	115 VAC 5 AMPS
	SEAL FAILURE	300 VAC 5 Ma	
VOLTAGE TOLERANCE	±10%		

HP	VOLTAGE	PHASE	NEMA CODE	SF	NAME PLATE AMPS	SF AMPS	LOCK ROTOR AMPS	RUN KW	START KVA	RUN KVA	NEMA REQ PREMIUM EFFICIENCY AT FL	MOTOR EFF AT SF*	MOTOR EFF AT FL*	MOTOR EFF AT 75% FL*	MOTOR EFF AT 50% FL*	POWER FACTOR AT SF	POWER FACTOR AT FL	POWER FACTOR AT 75% FL	POWER FACTOR AT 50% FL
75	460	3	G	1.3	96	120	570	67.8	453.6	76.4	95.4	94	95.4	94	93	0.88	0.887	0.886	0.84
	575				76.8	96.0	456												
100	460	3	H	1.3	125	155	826	88.1	657.5	99.5	95.4	94	95.4	94	93	0.884	0.886	0.877	0.845
	575				100.0	124.0	661												
125	460	3	H	1.3	152	190	1137	107.4	846.5	121.4	95.4	94.1	95.4	94.1	93.9	0.882	0.885	0.87	0.82
	575				122.0	152.0	851												

*Motor efficiency does not include seal and oil losses per IEC60034-30 5.1.3. Full load amps and service factor amps do include these losses.

1101 Myers Parkway
Ashland, OH 44805
Ph: 855.274.8947
Fx: 800.426.9446

490 Pinebush Rd., Unit 4
Cambridge, Ontario N1T 0A5, Canada
Ph: 800.363.7867
Fx: 888.606.5484

pentair.com